

Technical specifications - Jabra Pro 9400 Series



Product name	Jabra Pro 9450	Jabra Pro 9460/Pro 9465	Jabra Pro 9470
Packaging dimensions (L x W x H)	Master carton: 598 x 250 x 479mm Unit box (L-shape): 232 x 189 x (87-58)mm	Master carton: 598 x 250 x 479mm Unit box (L-shape): 232 x 189 x (87-58)mm	Master carton: 600 x 316 x 399mm Unit box (L-shape): 281 x 181 x (87-58)mm
Main unit dimension (L x W x H)	Base: 160 x 94 x 82mm Headset Basic: 130x48x18mm Headset Flex: 163 x 48 x 18mm Headset Duo: 165 x 165 x 35mm	Pro 9460: Base: 160 x 94 x 82mm Headset Flex: 163 x 48 x 18mm Headset Duo: 165 x 165 x 35mm	Pro 9465: Base: 160 x 94 x 82mm Headset Duo: 165 x 165 x 35mm
Weight	Base: 275g Headset Basic: 28g Headset Flex: 31g Headset Duo: 70g	Pro 9460: Base: 197g Headset Flex: 31g Headset Duo: 70g	Pro 9465: Base: 197g Headset Duo: 70g
What's in the box	1. Warning and declaration 2. Quick start guide 3. Headset 4. Base 5. Charger 6. USB cable 7. Flat cable 8. Earhook (Pro 9450 mono only)	1. Warning and declaration 2. Quick start guide 3. Headset 4. Base 5. Charger 6. USB cable 7. Flat cable 8. Earhook (9460 mono only)	1. Warning and declaration 2. Quick start guide 3. Headset 4. Base 5. Charger 6. USB cable 7. Flat cable 8. Earhook and neckband
Battery included	Yes	Yes	Yes
Charging time	120 min	120 min	120 min
AC power supply	Yes	Yes	Yes
Certifications	CE, CB, FCC, IC, NOM, NTC, EAC, PSB, ICASA, TELEC, SIRIM, ACMA, NZ Telepermit, UL, TCO, Bluetooth® (Pro 9465 /9470 only), DECT Security		
Warranty	North America: 1 year limited warranty Europe/APAC: 2 year limited warranty	North America: 1 year limited warranty Europe/APAC : 2 year limited warranty	North America: 1 year limited warranty Europe/APAC : 2 year limited warranty
Bluetooth® device	N/A	Pro 9460: N/A Pro 9465: Yes	Yes
Bluetooth® wireless technology	N/A	Pro 9460: N/A Pro 9465: Bluetooth® 2.1	Bluetooth® 2.1
Supported Bluetooth® modes	N/A	Pro 9460: N/A Pro 9465: SCO, eSCO, Sniff mode	SCO, eSCO, Sniff mode
Supported Bluetooth® profiles	N/A	Pro 9460: N/A Pro 9465: Headset and Hands-free	Headset and Hands-free
Pairing PIN	N/A	Pro 9460: N/A Pro 9465 Bluetooth®: 0000	Bluetooth®: 0000
DECT Device	Yes	Yes	Yes
Operating range	Up to 150m/490ft	Up to 150m/490ft	Up to 150m/490ft
Headset bandwidth	Narrowband and Wideband	Narrowband and Wideband	Narrowband and Wideband
Connection (mini jack, USB, etc)	Micro USB, mini jack for Busylight, RJ-9 for handset, RJ-9 for desk phone audio, RJ-45 for AUX		
Talk time	Up to 10 hours	Up to 10 hours	Up to 9 hours
Standby time	Up to 38 hours	Up to 38 hours	Up to 38 hours
Speaker Size	Mono: 1pcs Ø 28mm x 4.5mm/Duo: 2pcs Ø 23mm x 6.3mm		
Speaker sensitivity	Mono: 93dB +/-3dB/60mV at 1kHz/Duo: 97dB +/-3dB/60mV at 1kHz		
Speaker impedance	32 Ω +/-15% at 1kHz	32 Ω +/-15% at 1kHz	32 Ω +/-15% at 1kHz
Speaker Max output power	<118 dB SPL(A)	<118 dB SPL(A)	<118 dB SPL(A)
Speaker frequency range	150 – 6,800Hz	150 – 6,800 Hz	150 – 6,800 Hz
Microphone type	Basic/Flex/Duo: Uni-directional	Flex/Duo: Uni-directional	Advanced: 2pcs. Omni-directional for Noise Blackout™
Microphone sensitivity	Basic: -30+/-2dB V/Pa Flex/Duo: -34+/-2dB V/Pa	Flex/Duo: -34+/-2dB V/Pa	Advanced: -44+/-2dB V/Pa
Microphone frequency range	150Hz – 6,800Hz	150Hz – 6,800Hz	150Hz – 6,800Hz

Additional information

Operating temperature	+10°C to +40°C (non condensing)	+10°C to +40°C (non condensing)	+10°C to +40°C (non condensing)
Storage temperature	0°C -to +60°C (non condensing)	0°C -to +60°C (non condensing)	0°C -to +60°C (non condensing)
Security	DSAA + DSC	DSAA + DSC	DSAA + DSC
Power consumption	7.5V/650mA	7.5V/650mA	7.5V/650mA
Current consumption microphone	≤150µA	≤150µA	≤500µA
Battery status % after 30 min/60 min	25% after 30 min and 50% after 60 min	25% after 30 min and 50% after 60 min	25% after 30 min and 50% after 60 min
Charging plug dimensions	Ø 2.35mm	Ø 2.35mm	Ø 2.35mm

## Technical specifications - Jabra Pro 9400 Series



Product name	Jabra Pro 9450	Jabra Pro 9460/Pro 9465	Jabra Pro 9470
Material used	Polycarbonate/Akrylonitril-butadien-styren (PC/ABS): CYCOLOY C1200HF, GY6A288 Thermoplastic Polyurethanes - TPU: Desmopan 445 Acetal (POM) Copolymer: POM M90 Thermoplastic vulcanizates (TPVs): Santoprene TPV 201-87 Thermoplastic vulcanizates (TPVs) : PP/EPDM Shore A73 Polybutylene Terephthalate (PBT): PBT S600F20 Thermoplastic Elastomer (TPE): TPE Hytrel 6356 Polycarbonate (PC): LEXAN 121R-111		
Features	Crystal clear sound, remote asset management, HD Voice – wideband audio, remote call control, SafeTone™, PeakStop™, multi-device connectivity including smartphone and tablet-ready (Jabra Pro 9465/9470 only), UC Plug-And-Play, up to 150 meter wireless freedom, DECT Security Variant dependent: Noise Blackout™/Noise Canceling™ microphone		
Software Applications	Jabra Direct - enables Remote Call Control over most softphones/Jabra Xpress™ - remote mass deployment and management of Jabra USB audio devices		

SKU number	Description	UPC	EAN
9450-25-507-101	Jabra Pro 9450 EMEA	1.88-1.9 GHz EU standard DECT	5706991012637
9450-25-507-102	Jabra Pro 9450 UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991012644
9450-25-507-102-UK	Jabra Pro 9450 UK	1.88-1.9 GHz EU standard DECT	5706991018295
9450-25-507-103	Jabra Pro 9450 AU/NZ	1.88-1.9 GHz EU standard DECT	5706991012651
9450-25-707-101	Jabra Pro 9450 Flex EMEA	1.88-1.9 GHz EU standard DECT	5706991009712
9450-25-707-102	Jabra Pro 9450 Flex UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991009729
9450-25-707-106	Jabra Pro 9450 Flex JP	1.89-1.9 GHz Japan DECT	5706991014334
9450-29-707-101	Jabra Pro 9450 Duo EMEA	1.88-1.9 GHz EU standard DECT	5706991009767
9450-29-707-102	Jabra Pro 9450 Duo UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991009774
9450-65-507-105	Jabra Pro 9450 NCSA	1.92-1.93 GHz US DECT 6.0	5706991012668
9450-65-707-105	Jabra Pro 9450 Flex NCSA	1.92-1.93 GHz US DECT 6.0	5706991009743
9450-65-707-105-DC	Jabra Pro 9450 Mono NC Flex Boom, DC	1.92-1.93 GHz US DECT 6.0	5706991019421
9450-69-707-105	Jabra Pro 9450 Duo NCSA	1.92-1.93 GHz US DECT 6.0	5706991009798
9450-69-707-105-DC	Jabra Pro 9450 Duo NC Flex Boom, DC	1.92-1.93 GHz US DECT 6.0	5706991019438
9460-25-707-101	Jabra Pro 9460 EMEA	1.88-1.9 GHz EU standard DECT	5706991010671
9460-25-707-102	Jabra Pro 9460 UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991010688
9460-25-707-103	Jabra Pro 9460 AU/NZ	1.88-1.9 GHz EU standard DECT	5706991010695
9460-29-707-101	Jabra Pro 9460 Duo EMEA	1.88-1.9 GHz EU standard DECT	5706991010626
9460-29-707-102	Jabra Pro 9460 Duo UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991010633
9460-29-707-103	Jabra Pro 9460 Duo AU/NZ	1.88-1.9 GHz EU standard DECT	5706991010640
9460-65-707-105	Jabra Pro 9460 NCSA	1.92-1.93 GHz US DECT 6.0	5706991010701
9460-69-707-105	Jabra Pro 9460 Duo NCSA	1.92-1.93 GHz US DECT 6.0	5706991010657
9465-29-804-101	Jabra Pro 9465 Duo EMEA	1.88-1.9 GHz EU standard DECT	5706991012675
9465-29-804-102	Jabra Pro 9465 Duo UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991012682
9465-69-804-105	Jabra Pro 9465 Duo NCSA	1.92-1.93 GHz US DECT 6.0	5706991012699
9470-26-904-101	Jabra Pro 9470 EMEA	1.88-1.9 GHz EU standard DECT	5706991009866
9470-26-904-102	Jabra Pro 9470 UK/HK/SG	1.88-1.9 GHz EU standard DECT	5706991009873
9470-26-904-103	Jabra Pro 9470 AU/NZ	1.88-1.9 GHz EU standard DECT	5706991009880
9470-66-904-105	Jabra Pro 9470 NCSA	1.92-1.93 GHz US DECT 6.0	5706991009897
GSA9450-65-507-105	Jabra Pro 9450 NCSA	1.92-1.93 GHz US DECT 6.0	
GSA9460-65-707-105	Jabra Pro 9460 NCSA	1.92-1.93 GHz US DECT 6.0	
GSA9470-66-904-105	Jabra Pro 9470 NCSA	1.92-1.93 GHz US DECT 6.0	