

Jabra GN9330e

How to connect my Jabra GN9330e with Aastra Open Phone 6771, 6773, 6775, 71, 73, 75, Aastra 6739i, Aastra 7434 and 7444

Prerequisite:

Jabra GN9330e + Jabra Link 14201-10

In combination with one of the following phones:

- Open Phone 6771 / 6773 / 6775 including IP (previous name: Open Phone 71 / 73 / 75 including IP)
- Aastra 6739i
- Aastra 7434 / 7444 IP

Connection:

Important: Please note that remote call control for the Jabra GN9330e is only supported from version "L" or the Date code 9/09.

1. Plug the 1-sided end of the DHSG cable marked blue into the socket of your phone marked with the "headset" symbol.
2. Insert the split end of the DHSG cable into the Jabra GN9330e base. Plug the RJ10 plug into the socket marked with a "phone" symbol and the RJ45 plug into the base socket of the Jabra GN9330e marked with "AUX".

Software setup:

Put the headset into the base and activate the "DHSG" mode.

Hold down the "phone" button on the base of the Jabra GN9330e for

approx. 6 seconds until the online display (blue LED) on the headset starts to flash. The current software is displayed to you by activating the volume controller in the form of the charge display (green LED).

LEDs from left to right:

LED 1 = RHL

LED 2 = DHSG


LED 3 = AEI

LED 4 = MSH

Thereafter, you can switch into the different software modes (LED 1-4) with the “volume” controller on the headset. To confirm the software has successfully installed, the base automatically switches back to charge mode after approx. 15 seconds.

Base setup:

Set the phone setup switch (A-G) to "A".



Phone setup:

Open Phone 71 Menu > User> Settings > Audio > Headset ON

Open Phone 73 / 75 including IP: Menu > Overall Menu> Phone Settings
> Headset ON

Headset answer/end:

As soon as the dial tone signal can be heard in the headset, you can answer the call by pressing the "answer/end" button on the headset; by pressing again the call is ended.

