

Jabra GN9330e

How to connect my Jabra GN9330e with Aastra Office 70 and 80 or Aastra 5370 and 5380

Prerequisite:

Jabra GN9330e + Jabra Link 14201-10

In combination with one of the following phones:

- Office 70 / 70 IP or 5370 IP
- Office 80 / 80 IP or 5380 IP

Connection:

Important: Please note that remote call control for the Jabra GN9330e is only supported from version "L" or the Date code 9/09.

1. Plug the 1-sided end of the DHSG cable marked blue into the socket of your phone marked with the "headset" symbol.
2. Insert the split end of the DHSG cable into the Jabra GN9330e base. Plug the RJ10 plug into the socket marked with a "phone" symbol and the RJ45 plug into the base socket of the Jabra GN9330e marked with "AUX".

Software setup:

Put the headset into the base and activate the "DHSG" mode.

Hold down the "phone" button on the base of the Jabra GN9330e for approx. 6 seconds until the online display (blue LED) on the headset starts to flash. The current software is displayed to you by activating the volume controller in the form of the charge display (green LED).

LEDs from left to right:

LED 1 = RHL

LED 2 = DHSG


LED 3 = AEI

LED 4 = MSH

Thereafter, you can switch into the different software modes (LED 1-4) with the “volume” controller on the headset. To confirm the software has successfully installed, the base automatically switches back to charge mode after approx. 15 seconds.

Base setup:

Set the phone setup switch (A-G) to "A".



Phone setup:

Menu > User> Settings > Audio > Headset ON

From Release 7.9: Menu> Settings> Audio> Headset> Headset ON

Headset answer/end:

As soon as the dial tone signal can be heard in the headset, you can answer the call by pressing the "answer/end" on the headset; by pressing again the call is ended.

