

Jabra GN9350e

How to connect my Jabra GN9350e with Alcatel IP Touch 4028 EE, 4038 EE, 4068 EE

Jabra GN9350e +Jabra Link 14201-20

In combination with one of the following phones:

- IP Touch 4028 EE
- IP Touch 4038 EE
- IP Touch 4068 EE

EE = Extended Edition

Connection:

Connect the EHS adapter to the GN9350e base as follows:

1. Insert the supplied RJ10 to RJ10 connection cable into the socket of your Jabra GN9350 base marked "phone" and the other end into the socket of the EHS adapter marked with the "phone" symbol.
2. Now connect the end of the RJ45 to RJ45 connection cable (EHS adapter) marked in red with the socket of the EHS adapter marked with "AUX" and the socket of your Jabra GN9350e base marked with "AUX".
3. Now connect the white RJ10 to the 3.5 mm jack connection cable marked "D" to the socket of the EHS adapter marked with "Headset/Handset" and with the Headset socket of your phone.
4. Now connect the orange RJ12 to RJ12 connection cable marked with "A" to the socket of the EHS adapter marked with "COM" and with the "bell" socket of your phone.

Please note that full functionality is only available when all the color-

marked parts of the cables are inserted into the EHS adapter, see photo.




Software setup:

In the LCD Display, set the Jabra GN9350 to "DHSG" and press the OK button to confirm the software setting.



Base setup:

Set the phone setup switch (A-G) to "A".



Headset answer/end:

As soon as the dial tone signal can be heard in the headset, you can answer the call by pressing the "answer/end" button on the headset; by pressing again the call is ended.



Phone setup with system software version 9.xx and higher:

No settings are required on the phone for the use of a headset. Following the correct adaptation of the audio jack, a headset symbol should appear in the “Phone display”. If the headset symbol does not appear, please check the following settings:

Menu> Settings> Phone> Audio Jack> Select / Activate Headset.

Phone setup with system software version below version 9.xx:

Important: The “**Force Headset**” function must not be activated on the phone, as otherwise it will not be possible to accept external calls!

Menu> Settings> Phone> Audio Jack> Force Headset OFF

Menu> Settings> Phone> Socket > Activate Headset

Ringtone transfer / phone setup:

Important: The dial tone signal in the headset is only transmitted if one of the following ringtones is used, e.g., Standard / Classic / Cold River / Dooing-Dooing. > Menu> Settings> Dial Tone > Internal / External

Should the dial tone signal transfer not work although you have setup the correct ringtone, please check the following settings:

Menu > Settings > Phone > Internal/External, More Options

No sound, Progressive, Beeps> all points must be set to "OFF".