

Jabra GN9350e MS

How to connect my Jabra GN9350e with Siemens Opti Point 410, 420, 500, 600

Prerequisite:

Jabra GN9350 + Jabra Link 14201-10 + Acoustic-Adapter (only available from Siemens)

In combination with one of the following phones:

- OptiPoint 410 standard / advance
- OptiPoint 420 standard / advance
- OptiPoint 500 basic / standard / advance
- OptiPoint 600

+ OptiPoint Acoustic Adapter:

- min. Version number for: S30817-K7110-B508 -10
- min. Version number for: S30817-K7110-N508 -1

+ HiPath phone system:

- HiPath 500 from V.5
- HiPath 1220 from V2.1 Build 032
- HiPath 2000 from V1.0
- HiPath 3000 from V3 SMR 14
- HiPath 3000 from V4 SMR 7
- HiPath 4000 from V1

Important: If any of the components are missing the remote call control will not work.

Connection:

1. Plug the 1-sided end of the DHSG cable marked blue into the socket of the OptiPoint Acoustic Adapter marked with the “headset” symbol.
2. Insert the RJ10 plug into the socket marked with a “phone” symbol and the RJ45 plug into the base socket of the Jabra GN9350 marked with "AUX".



Software setup:

In the LCD Display, set the Jabra GN9350 to "DHSG" and press the OK button.



Base setup:

Set the phone setup switch (A-G) to "A".



Microphone level setup:

We recommend setting the microphone volume in the LCD display to 7 out of 12.



Phone setup:

Important: As soon as the headset is connected + setup, a reset must be performed on the OptiPoint, for the EHS function to activate.

An optional headset button can be installed over the phone menu (combination: *91 > Select Button > Change Button > Headset > OK).

Headset answer/end:

As soon as the dial tone signal can be heard in the headset, you can answer the call by pressing the "answer/end" button on the headset; by pressing again the call is ended.

