

Jabra Link 14201-10

How to connect my Jabra Pro 92x with Siemens OpenStage 30, 40, 60, 80

Prerequisite:

Jabra Pro 92x + Jabra Link 14201-10

In combination with one of the following phones:

- Siemens OpenStage 30/40/60/80

Full function from software version 1.40 (multiple dial tone signal transfer)

Connection:

1. Plug the 1-sided end of the DHSG cable marked blue into the socket of the phone marked with the “headset” symbol.
2. Plug the RJ10 plug into the socket marked with the “phone” symbol and the RJ45 plug into the base socket marked with "AUX".


Now you can setup the headset for your phone with the automatic or manual configuration.

Automatic configuration:

To start the automatic configuration, please let someone call you on this phone; wait at least 10 seconds before you pick up the phone. Now the appropriate EHS mode should be set up.


If the automatic configuration did not work, please manually select the DHSG mode. See User Manual for instructions.

Base setup:



Set the phone setup switch to position "A".

Microphone level setup:



Put on the headset and call a colleague, for example.

Now you can select the desired microphone volume using the +/- button.

Phone setup:

Important: For the equipment software 3.18, the headset operation must be set up additionally at the phone.

Menu > User > Audio > Settings > Headset > Cordless > OK

Important: The dial tone signal in the headset is transmitted only if the standard ringtones are used. There is no dial tone signal transfer for



mp3.