

Jabra Link 14201-10

How to connect my Jabra GN9330e with Siemens OpenStage 30, 40, 60, 80

Prerequisite:

Jabra GN9330e + Jabra Link 14201-10

In combination with one of the following phones:

- OpenScape 30 / 40 / 60 / 80

Important:

Please note that Remote Call Control is only supported by the Jabra GN9330e from version "L" or from date code 9/09.

Connection:

1. Plug the 1-sided end of the DHSG cable marked blue into the socket marked with a "headset" symbol on your phone.
2. Plug the RJ10 plug into the socket with the "phone" symbol and the RJ45 plug into the socket on the Jabra GN9330e base marked with "AUX".

EHS setup:

1. Place the headset on the base and activate "DHSG" mode.
2. Hold down the "phone" button on the base of the Jabra GN9330e for approx. 6 seconds until the online display (blue LED) on the headset starts to flash. The current EHS is displayed to you by activating the speaker controller in the form of the charge display (green LED).

LEDs from left to right:

LED 1 = RHL

LED 2 = DHSG


LED 3 = AEI

LED 4 = MSH

Thereafter, you can switch into the different EHS modes (LED 1-4) with the “ volume” controller on the headset. To confirm the EHS has successfully installed, the base automatically switches back to charge mode after approx. 15 seconds.

Base setup:

Set the phone set-up switch (A-G) to " A".



Answer/end calls on the headset:

Once the dial tone signal can be heard in the headset, you can answer the call by pressing the " Answer/end" button on the headset, while pressing it again will end the call.



Phone setup:

Important: For equipment EHS 3.18, the headset operation must be set up additionally at the phone.

OpenStage 40: Menu > Audio accessories > Headset > Cordless

OpenStage 60/80: Menu > User > Audio > Settings > Headset > Cordless

Important: The dial tone signal in the headset is transmitted only if the standard ring tones are used on your phone. There is no dial tone signal transfer for mp3 ring tones.