

Jabra Link 14201-20

How to connect my Jabra Pro 92X with Alcatel IP Touch 4028 EE, 4038 EE, 4068 EE

Prerequisite:

Jabra Pro 92x + Jabra Link 14201-20

In combination with one of the following phones:

- IP Touch 4028 EE
- IP Touch 4038 EE
- IP Touch 4068 EE

EE = Extended Edition

Connection:

1. Take the supplied connection cable RJ10 to RJ10 of the Jabra Pro 92x and insert into the socket of your Jabra Pro 92x base marked "phone" and the other end into the socket of the EHS adapter marked with the "phone" symbol.
2. Now connect the end of the RJ45 to RJ45 connection cable (EHS adapter) marked in red with the socket of the EHS adapter marked with "AUX" and the socket of your Jabra Pro 92x base marked with "AUX".
3. Now connect the white RJ10 to the 3.5 mm jack connection cable marked "D" to the socket of the EHS adapter marked with "Handset / Headset" and with the "headset" socket of your phone.
4. Now connect the orange RJ12 to RJ12 connection cable marked with "A" to the socket of the EHS adapter marked with "COM" and with the "bell" socket of your phone.

Please note that full functionality is only available when all the color-marked parts of the cables are inserted into the EHS adapter. See photo.




Now you can setup the headset for your phone with the automatic or manual configuration.

Automatic configuration:

To start the automatic configuration, please let someone call you on this phone; wait at least 10 seconds before you pick up the phone. Now the appropriate EHS mode should be set up.


If the automatic configuration did not work, please manually select the DHSG mode. See User Manual.

Base setup:



Set the phone setup switch to position "A".

Microphone volume setting:



Put on the headset and call a colleague, for example.

Now you can select the desired microphone volume using the +/- button.

Phone setup with system software 9.xx and higher:

No settings are required on the phone for the use of a headset.

Following the correct adaptation of the audio jack, a headset symbol should appear in the “Phone display”. If the headset symbol does not appear, please check the following settings:

Menu> Settings> Phone> Audio Jack> Headset Activate/Select.

Phone setup with system software lower than 9.xx:

Important: The “Force Headset” function must not be activated on the phone, as otherwise it will not be possible to accept external calls!

Menu> Settings> Phone> Audio Jack>Force Headset OFF

Menu> Settings> Phone> Socket > Activate Headset

Dial tone transfer / phone setup:

Important: The dial tone signal in the headset is only transmitted if one of the following ringtones is used, e.g. Standard/ Classic / Cold River / Dooing-Dooing. > Menu> Settings> Dial Tone > Internal / External

Should the dial tone signal transfer not work although you have setup the correct ringtone, please check the following settings:

Menu > Settings > Phone > Internal/External, more options

No sound, Progressive, Beeps> all points must be set to "OFF".